

## **Nylon Fasteners**

## Shoulder Washers

Standard Sizes





	Nylon Shoulder Washers											
Nominal Washer Size	OD Outside Diameter		ID Inside Diameter		S Shoulder Thickness		T Small Section Thickness		W Small Section Width			
											Max	Min
	2	.255	.245	.098	.088	.045	.035	.045	.035	.161	.151	
4	.286	.276	.127	.117	.045	.035	.045	.035	.192	.182		
6	.333	.323	.151	.141	.045	.035	.045	.035	.223	.213		
8	.380	.370	.179	.169	.055	.045	.055	.045	.255	.245		
10	.442	.432	.206	.196	.055	.045	.055	.045	.286	.276		
1/4	.567	.557	.265	.255	.065	.055	.065	.055	.380	.370		

Description	An integrally-formed nylon disk that has a centrally located hole, with a sleeve that has the same internal diameter as the washer, but has an outside diameter which is less than that of the washer's base.					
Applications/ Advantages	Used to insulate screws, rivets or shafts from panels in electrnic applications. May also be used as a bushing in mechanical applications to reduce friction between parts.					
Material	Nylon 6/6					
Hardness	Rockwell M80					
Thermal Properties	Melting Point: 500° F Continuous Use Temperature: 185° F					