

WOOD SCREWS

DEEP THREAD

Round Washer Head w/ Phillips Recess





ROUND WASHER PHILLIPS RECESS DEEP THREAD WOOD SCREW												
Nominal Diameter	A		В	н		Р		D		т		Recess Size
	Washer Diameter		Head Diameter	Total Head Height		Recess Depth		Major Diameter		Threaded Length		
	Max	Min	Ref	Max	Min	Max	Min	Max	Min	L≤1"	L > 1"	
8	0.380	0.358	0.259	0.113	0.101	0.076	0.048	0.169	0.159	Full thread	2/3 thread	#2
Tolerance on Length		Up to 5/8"						+0 / -0.03				
		Over 5/8 to 1.5"						+0 / -0.05				
		Over 1.5 to 2.75"								+0 / -0.06		
		Over 2.75 to 5"						+0 / -0.09				

Description	An externally threaded fastener with a dome-shaped head and an integrally formed washer; a recess that can accomodate a Phillips screw- driver; and a single lead thread. The shank has a reduced diameter.					
Applications / Advantages	The deeper thread design offers greater resistance to pull-out forces. The round washer head is preferable in softer woods and offers a greater bearing surface than a countersunk design. It is superior to countersunk or pan heads at pulling material together.					
Material	C1022 case-hardened steel					
Surface Hardness	Rockwell C 45 minimum					
Case Depth	0.004" - 0.009"					
Torque	#8 Diameter: 35 kg/cm minimum #10 Diameter: 50 kg/cm minimum					
Plating	See Appendix-A for plating information					